

# Jet Wash7

7x20W RGBW moving wash light with a 4° - 55° zoom



## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 7x20W RGBW Osram Ostar LEDs
- Luminous flux: (4°) 1'232 lm - (55°) 1'993 @Full
- Lux: (4°) 28'754 lx - (55°) 611lx @3 m full
- Source life expectancy: > 50.000 hrs (L70B10 @Ta 25° C / 77° F)

### OPTICS

- Zoom range: 4° - 55° motorised linear zoom
- Lens type: honeycomb gapless plano-convex optics

### COLOUR SYSTEM

- Colour mixing: RGBW / FC
- CCT: CCT control, + / - green correction, tungsten emulation
- White presets: 2.800 K ~ 10.000K
- Colour wheel: virtual colour wheel with macros

### DYNAMIC EFFECTS

- Control Resolution: 16-bit dimmer
- Special features: linear crossfade channel from any white to any colour; virtual CTO on colours

### BODY

- Hardware on-board: sockets for quick-Lock Omega bracket (clamp not included)
- Pan range: 540°
- Tilt range: 233°
- Pan/Tilt resolution: bit 16-bit
- Feedback: automatic repositioning after accidental movement
- Body: aluminium structure with high-resistance polycarbonate cover
- Body colour: see variants

### CONTROL

- Protocols: DMX512, RDM
- DMX channels: 23channel
- RDM: RDM for remote monitoring and settings
- Display: LCD high resolution colour display with autotrim
- Firmware upgrade: via DMX with UPBOXPRO/UPBOX2 (USB-DMX interface not included)

## ACCESSORIES & RELATED PRODUCTS

- OS24PLUS Quick-lock omega bracket, M12 hole
- TOUR53415L03 Dmx cable HC5340. CANC5MXX XLR 5p->CANC5FXX XLR (f) 5p, L.3m
- 958225L03 3x2.5mm TH07 Cable, 16A 3p PwCon MXW, 16A 3p PwCon FXW, L. 3m
- 9513FXWL03 Ass. 3x2.5mm TH07 cable, 16A 3p 230V CEE plug, MENAC3FXW socket, L.3 m
- 9533FXWL03 Ass. 3x2.5mm TH07 cable, SHUKO plug, MENAC3FXW socket, L.3m

The **Jet Wash7** is a compact and fast LED moving wash light with motorized zoom control. The 20W Osram RGBW LED source provides plenty of output and combined with a highly efficient optical system capable of zooming from 4° to 55°, this unit can easily work as beam or wash light. The **Jet Wash7**'s colour mixing system features precise and advanced control with superior white and saturated tones, and a clean and intuitive user interface similar to the other series.

## MAIN FEATURES

- Compact form factor and fast movements
- Zoom from 4° to 55° with high optical efficiency
- Precise white CCT and colour mixing

## VERSIONS

Code	Housing
JETWASH7	Black
JETWASH7WH	White

## ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: 4 selectable dimming modes available
- Strobe / shutter: 1 - 30 Hz, electronic
- Operating temperature: -10° ~ +45° Ta
- LED Control: flicker free operation
- Selectable PWM: 600 ~ 50.000 Hz

## ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 160W
- Standby power: 35W
- Output (at 230V): 15 units on a single power line
- Power factor: > 0,94

## PHYSICAL

- IP rating: IP20
- Cooling: filtered forced-air cooling with low-noise fans
- Suspension and fixing: any position with quick-lock omega brackets
- Signal connection: Amphenol XLR 5p IN/OUT connectors
- Power connection: Neutrik powerCON TRUE1 IN/OUT connectors
- Dimensions (WxHxD): 279x377x205mm / 10.98"x14.84"x8.07"
- Weight: 8,3kg / 18.3lbs


## CERTIFICATIONS / APPROVALS

- Certifications / Approvals: CE, UKCA, RCM



- RSR0630B Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black
- C6002B Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black
- FCLASTRAW7PIX Flight case for 6 pcs of ASTRAWASH7PIX
- ASTRAWASH7PEC Egg Crate for ASTRAWASH7PIX
- UPBOXPRO Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

**PRESET FULL ON**

Beam angle 50%: 4°


**PRESET FULL ON**

Beam angle 50%: 55°


**TECHNICAL DRAWINGS**

**CERTIFICATIONS / APPROVALS**

 Visit our website  
 for specifications and  
 tech documentations
